

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/047123 A1

(51) International Patent Classification⁷: **H01B 7/08**

(21) International Application Number:
PCT/GB2003/004990

(22) International Filing Date:
18 November 2003 (18.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0227206.0 21 November 2002 (21.11.2002) GB

(71) Applicant (for all designated States except US): **QINETIQ LIMITED** [GB/GB]; Registered Office, 85 Buckingham Gate, London SW1E 6PD (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LUDLOW, Jeremy, Leonard, Clive** [—/GB]; QinetiQ Limited, Cody Technology Park, Building A7 Room G010, Ively Road, Farnborough, Hampshire GU14 0LX (GB). **MAYLIN,**

Mark, Gregory [GB/GB]; QinetiQ Limited, Cody Technology Park, Building A7 Room G059, Ively Road, Farnborough, Hampshire GU14 0LX (GB). **ROGERS, Michael, Clive** [GB/GB]; 9 Vespasian Gardens, Basingstoke, Hampshire RG24 9SN (GB).


(74) Agent: **OBEE, Robert, W.**; IP QinetiQ Formalities, Cody Technology Park, A4 Building, Room G016, Ively Road, Farnborough, Hampshire GU14 0LX (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: ELECTRICAL TRANSMISSION SYSTEM



(57) **Abstract:** A system for the transmission of electrical energy between different parts of an electrically conductive structure, and in particular for transmission of power and/or data signals to/from downhole equipment or instrumentation in oil and gas wells. A first layer of electrically insulative ceramic material (5) is deposited on the structure (e.g. oil pipe string 3A), followed by a series of electrically conductive tracks (6) and a second layer of electrically insulative ceramic material (7). The tracks (6) which serve for the transmission of power and/or data signals are thus sandwiched between the layers (5 and 7), insulated from the structure (3A) and the external environment and protected from damage. Each layer (5, 6 and 7) is deposited by a thermal spray process such as plasma spraying or high velocity oxy fuel spraying.

WO 2004/047123 A1